

PAF2520A Air curtain Pamir

Article number: 246834



Description

Slim air curtain for entrances, with energy-efficient control.

Pamir 2500 has a recommended installation height of 2,5 m and is designed for horizontal mounting in shops, offices and public premises. The air curtain together with the intelligent FC control system allows you to easily optimize your comfort and save energy.

The recommended installation height varies depending on the relevant premises.

The control system is ordered separately.



Technical parameters

Installation		
Maximum installation height	2,500	mm
Nominal data		
Color casing	Traffic white	
Color casing, RAL	RAL 9016	
Color, outlet grilles	Telegrey 2	
Color outlet grilles, RAL	RAL 7046	
Color name, glass		
Enclosure class	IP21	
Ambient working temperature (dry conditions)	-20 to 30 °C	
Dimensions and weights		
Length	2,050	mm
Height	210	mm
Depth	345	mm
Weight	30	kg
Air flow		
Air flow	2600; 2200; 1800	m ³ /h
Sound data		
Sound level	55; 50; 44	dB(A)
Sound power level LWA	72	dB(A)
Motor/control supply		
Control/motor supply	230	V
Phases, motor	1~	
Control/motor current	1	A
Frequency	50; 60	Hz
Input power (P1), motor	230	W

Accessories

PA2P20 Pendulum bar (19569)
PA2PF20 Pendulum brackets (19417)
PA34TR20 Threaded bars (18057)

Documents

Catalogue pages Pamir 2500
Manual Pamir 2500
Declaration of Conformity PAF2500
UKCA Declaration of Conformity PAF2500
Exploded view PAF25-32