



Description

Slim air curtain for entrances, with energy-efficient control.

Pamir 2500 has a recommended installation height of 2,5 m and is designed for horizontal mounting in shops, offices and public premises. The air curtain together with the intelligent FC control system allows you to easily optimize your comfort and save energy.

The recommended installation height varies depending on the relevant premises.

The control system is ordered separately.

Technical parameters

Installation		
Maximum installation height	2,500	mm
Nominal data		
Color casing	Traffic white	
Color casing, RAL	RAL 9016	
Color, outlet grilles	Telegrey 2	
Color outlet grilles, RAL	RAL 7046	
Color name, glass		
Enclosure class	IP20	
Ambient working temperature (dry conditions)	-20 to 30	°C
Dimensions and weights		
Length	1,560	mm
Height	210	mm
Depth	345	mm
Weight	26	kg
Air flow		
Air flow	2200; 1700; 1400	m³/h
Sound data		
Sound level	52; 48; 40	dB(A)
Sound power level LWA	9	dB(A)
Motor/control supply		
Control/motor supply	230	V
Control/motor current	0.7	A
Frequency	50; 60	Hz
Input power (P1), motor	155	W

Electric heat		
Input power, heater	12; 8; 4	kW
Current heating	17.3; 11.5; 5.6	A
Voltage heating	400	V
Phases	3~	
Temperature rise, maximum heat output, highest airflow	17	°C
Temperature rise, maximum heat output, middle airflow	21	°C
Temperature rise, maximum heat output, lowest airflow	26	°C

Parameter		
Power		12.00 kW
Air flow		2200 m³/h
Inlet air temperature		20 °C
Outlet air temperature		36 °C
Inlet air humidity		70.0 % r.H
Outlet air humidity		27.0 % r.H

Accessories

- PA2P15 Pendulum bar (19568)
- PA2PF15 Pendulum brackets (19415)
- PA34TR15 Threaded bars (18056)

Documents

- Catalogue pages Pamir 2500
- Manual Pamir 2500
- Declaration of Conformity PAF2500
- UKCA Declaration of Conformity PAF2500
- Exploded view PAF25-32