

PAF2515A Air curtain Pamir

Article number: 246830



Description

Slim air curtain for entrances, with energy-efficient control.

Pamir 2500 has a recommended installation height of 2,5 m and is designed for horizontal mounting in shops, offices and public premises. The air curtain together with the intelligent FC control system allows you to easily optimize your comfort and save energy.

The recommended installation height varies depending on the relevant premises.

The control system is ordered separately.



Technical parameters

Installation	
Maximum installation height	2,500 mm
Nominal data	
Color casing	Traffic white
Color casing, RAL	RAL 9016
Color, outlet grilles	Telegrey 2
Color outlet grilles, RAL	RAL 7046
Color name, glass	
Enclosure class	IP21
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	1,560 mm
Height	210 mm
Depth	345 mm
Weight	23 kg
Air flow	
Air flow	2100; 1700; 1250 m ³ /h
Sound data	
Sound level	54; 49; 44 dB(A)
Sound power level LWA	71 dB(A)
Motor/control supply	
Control/motor supply	230 V
Phases, motor	1~
Control/motor current	0.7 A
Frequency	50; 60 Hz
Input power (P1), motor	155 W

Accessories

PA2P15 Pendulum bar (19568)
PA2PF15 Pendulum brackets (19415)
PA34TR15 Threaded bars (18056)

Documents

Catalogue pages Pamir 2500
Manual Pamir 2500
Declaration of Conformity PAF2500
UKCA Declaration of Conformity PAF2500
Exploded view PAF25-32