

PAFEC4220WH Air curtain Pamir

Article number: 230367



Description

Stylish and energy-efficient air curtain for large commercial premises.

Pamir 4200 has a recommended installation height of 4,2 m and is equipped with energy-efficient EC motors which enable stepless control of the airflow. The air curtain together with the intelligent FC control system allows you to easily optimize your comfort and save energy.

The air curtain is available for horizontal, vertical and recessed installation. The recommended installation width of Pamir 4200 is 6 m with air curtains mounted on both sides of the opening.

The recommended installation height and width vary depending on the relevant premises.

The control system is ordered separately.

Find more details in our online catalogue

Technical parameters

Installation		
Maximum installation height	4,200	mm
Nominal data		
Color casing	Traffic white	
Color casing, RAL	RAL 9016	
Color, outlet grilles	Telegrey 2	
Color outlet grilles, RAL	RAL 7046	
Enclosure class	IP24	
Ambient working temperature (dry conditions)	-20 to 30	°C
Dimensions and weights		
Length	2,039	mm
Height	331	mm
Depth	611	mm
Weight	87.84	kg
Air flow		
Air flow	4600; 3700; 2200	m³/h
Sound data		
Sound level	65; 61; 47	dB(A)
Sound power level LWA	81	dB(A)
Motor/control supply		
Control/motor supply	230	V
Phases, motor	1~	
Control/motor current, 50 Hz	6	A
Input power (P1), motor 50Hz	1,030	W
Control/motor current, 60 Hz	6	A
Input power (P1), motor 60Hz	1,030	W
Water data		
Pressure drop water 80/60 °C, air +18 °C	14	kPa
Water temperature	max 110	°C
Maximum working pressure	16	bar
Dimension water connections	DN20	

Parameter		
Power		26.43 kW
Air flow		4600 m³/h
Inlet air temperature		20 °C
Outlet air temperature		37 °C
Water flow		0.323 l/s
Air pressure drop		31 Pa
Inlet air humidity		70.0 % r.H
Outlet air humidity		26.0 % r.H
Water pressure drop		13.0 kPa
Inlet fluid temperature		80 °C
Outlet water temperature		60 °C
Fluid		fluidType_0
Glycol		-

Accessories

AXP300 Hit protection (10028)	DTV200S Filter pressure guard (17597)
FCBA Control for air curtain (74687)	FCDA Control for air curtain (74684)
FCPA Control for air curtain (74686)	FCSA Control for air curtain (74685)
FHDN20 Flexible hose kit DN20 (18055)	FHDN2010 Flexible hose k. DN20 (88906)
PA34CB20 Ceiling brackets (18060)	PA34EF20 External inlet filter (19066)
PA34TR20 Threaded bars (18057)	PA34VD20 Vibration damper (18066)
PA34WB20 Wall brackets (18045)	PA34WS20 Wire suspension (18063)
PA4DCL Design kit ceiling (13560)	PA4DCM Design kit ceiling (13559)
PA4DCS Design kit ceiling (13557)	PA4DW20 Design kit wall (110840)
PA4DXT Design kit ceiling (13561)	PA4HE Extension hood PAFEC (FE10245)
PA4JK Vertical kit/Joining kit (110760)	PA4VDW20 Design kit vertical (110755)
PA4XT20 Outlet extension (19092)	PAWBL20 Wall brackets (214952)
VPFC15LF Valve system DN15LF (238293)	VPFC15NF Valve system DN15NF (238294)
VPFC20 Valve system DN20 (238295)	VPFC25 Valve system DN25 (238296)
VPFC32 Valve system DN32 (238297)	

Documents

Catalogue pages Pamir 4200
Manual Pamir 3500/4200/5000
Declaration of Conformity PAFEC4200
UKCA Declaration PAFEC4200
Exploded view PAFEC35-42-50