



Description

Stylish and energy-efficient air curtain for large commercial premises.

Pamir 4200 has a recommended installation height of 4,2 m and is equipped with energy-efficient EC motors which enable stepless control of the airflow. The air curtain together with the intelligent FC control system allows you to easily optimize your comfort and save energy.

The air curtain is available for horizontal, vertical and recessed installation. The recommended installation width of Pamir 4200 is 6 m with air curtains mounted on both sides of the opening.

The recommended installation height and width vary depending on the relevant premises.

The control system is ordered separately.

Find more details in our online catalogue

Technical parameters

Installation		
Maximum installation height	4,200	mm
Nominal data		
Color casing	Traffic white	
Color casing, RAL	RAL 9016	
Color, outlet grilles	Telegrey 2	
Color outlet grilles, RAL	RAL 7046	
Enclosure class	IP24	
Ambient working temperature (dry conditions)	-20 to 30	°C
Dimensions and weights		
Length	2,549	mm
Height	331	mm
Depth	611	mm
Weight	119.98	kg
Air flow		
Air flow	5600; 4700; 2700	m³/h
Sound data		
Sound level	66; 61; 48	dB(A)
Sound power level LWA	82	dB(A)
Motor/control supply		
Control/motor supply	230	V
Phases, motor	1~	
Control/motor current, 50 Hz	6.9	A
Input power (P1), motor 50Hz	1,200	W
Control/motor current, 60 Hz	6.9	A
Input power (P1), motor 60Hz	1,200	W

Water data		
Water heating full output 40/30 °C, air +18 °C	24	kW
Pressure drop water 40/30 °C, air +18 °C	7.5	kPa
Water temperature	max 110	°C
Maximum working pressure	16	bar
Dimension water connections	DN20	

Parameter		
Power	77.87	kW
Air flow	5600	m³/h
Inlet air temperature	20	°C
Outlet air temperature	61	°C
Water flow	0.950	l/s
Air pressure drop	80	Pa
Inlet air humidity	70.0	% r.H
Outlet air humidity	7.0	% r.H
Water pressure drop	15.7	kPa
Inlet fluid temperature	80	°C
Outlet water temperature	60	°C
Fluid	fluidType_0	
Glycol	-	

Accessories

AXP300 Hit protection (10028)	DTV200S Filter pressure guard (17597)
FCBA Control for air curtain (74687)	FCDA Control for air curtain (74684)
FCPA Control for air curtain (74686)	FCSA Control for air curtain (74685)
FHDN20 Flexible hose kit DN20 (18055)	FHDN2010 Flexible hose k. DN20 (88906)
PA34CB30 Ceiling Bracket (18061)	PA34EF25 External inlet filter (19067)
PA34TR30 Threaded bars (18058)	PA34VD30 Vibration damper (18067)
PA34WB30 Wall brackets (18046)	PA34WS30 Wire suspension (18064)
PA4DCL Design kit ceiling (13560)	PA4DCM Design kit ceiling (13559)
PA4DCS Design kit ceiling (13557)	PA4DW25 Design kit wall (110841)
PA4DXT Design kit ceiling (13561)	PA4HE Extension hood PAFEC (FE10245)
PA4JK Vertical kit/Joining kit (110760)	PA4VDW25 Design kit vertical (110756)
PA4XT25 Outlet extension (19093)	PAWBL30 Wall brackets (214953)
VPFC15LF Valve system DN15LF (238293)	VPFC15NF Valve system DN15NF (238294)
VPFC20 Valve system DN20 (238295)	VPFC25 Valve system DN25 (238296)
VPFC32 Valve system DN32 (238297)	

Documents

Catalogue pages Pamir 4200
Manual Pamir 3500/4200/5000
Declaration of Conformity PAFEC4200
UKCA Declaration PAFEC4200
Exploded view PAFEC35-42-50