

PAFEC5025WH Air curtain Pamir

Article number: 230389



Description

Stylish and energy-efficient air curtain for industrial premises.

Pamir 5000 has a recommended installation height of 5 m and is equipped with energy-efficient EC motors which enable stepless control of the airflow. The air curtain together with the intelligent FC control system allows you to easily optimize your comfort and save energy.

The air curtain is available for horizontal, vertical and recessed installation. The recommended installation width of Pamir 5000 is 7 m with air curtains mounted on both sides of the opening.

The recommended installation height and width vary depending on the relevant premises.

The control system is ordered separately.

Find more details in our online catalogue

Technical parameters

Installation		
Maximum installation height	5,000	mm
Nominal data		
Color casing	Traffic white	
Color casing, RAL	RAL 9016	
Color, outlet grilles	Telegrey 2	
Color outlet grilles, RAL	RAL 7046	
Enclosure class	IP24	
Ambient working temperature (dry conditions)	-20 to 30	°C
Dimensions and weights		
Length	2,549	mm
Height	331	mm
Depth	611	mm
Weight	96.18	kg
Air flow		
Air flow	6900; 5450; 1850	m ³ /h
Sound data		
Sound level	69; 63; 37	dB(A)
Sound power level LWA	85	dB(A)
Motor/control supply		
Control/motor supply	230	V
Phases, motor	1~	
Control/motor current, 50 Hz	9.1	A
Input power (P1), motor 50Hz	1,650	W
Frequency	50; 60	Hz
Input power (P1), motor 60Hz	1,650	W
Electric heat		
Voltage (nominal)	230	V

Water data	
Pressure drop water 80/60 °C, air +18 °C	4.3 kPa
Water temperature	max 110 °C
Maximum working pressure	16 bar
Dimension water connections	DN20

Parameter	
Power	36.02 kW
Air flow	6900 m³/h
Inlet air temperature	20 °C
Outlet air temperature	35 °C
Water flow	0.440 l/s
Air pressure drop	41 Pa
Inlet air humidity	70.0 % r.H
Outlet air humidity	28.0 % r.H
Water pressure drop	4.0 kPa
Inlet fluid temperature	80 °C
Outlet water temperature	60 °C
Fluid	fluidType_0
Glycol	-

Accessories

AXP300 Hit protection (10028)

FCBA Control for air curtain (74687)

FCPA Control for air curtain (74686)

FHDN20 Flexible hose kit DN20 (18055)

PA34CB30 Ceiling Bracket (18061)

PA34TR30 Threaded bars (18058)

PA34WB30 Wall brackets (18046)

PA4DCL Design kit ceiling (13560)

PA4DCS Design kit ceiling (13557)

PA4DXT Design kit ceiling (13561)

PA4JK Vertical kit/Joining kit (110760)

PA4XT25 Outlet extension (19093)

VPFC15LF Valve system DN15LF (238293)

VPFC20 Valve system DN20 (238295)

VPFC32 Valve system DN32 (238297)

DTV200S Filter pressure guard (17597)

FCDA Control for air curtain (74684)

FCSA Control for air curtain (74685)

FHDN2010 Flexible hose k. DN20 (88906)

PA34EF25 External inlet filter (19067)

PA34VD30 Vibration damper (18067)

PA34WS30 Wire suspension (18064)

PA4DCM Design kit ceiling (13559)

PA4DW25 Design kit wall (110841)

PA4HE Extension hood PAFEC (FE10245)

PA4VDW25 Design kit vertical (110756)

PAWBL30 Wall brackets (214953)

VPFC15NF Valve system DN15NF (238294)

VPFC25 Valve system DN25 (238296)

Documents

Catalogue pages Pamir 5000

Manual Pamir 3500/4200/5000

Declaration of Conformity PAFEC5000

UKCA Declaration PAFEC5000

Exploded view PAFEC35-42-50