

ARFEC3510WLL Air curtain Arden

Article number: 190547



Description

Recessed energy-efficient air curtain for commercial premises.

Arden 3500 is designed for recessed installation with a recommended installation height of 3,5 m and is equipped with energy-efficient EC motors which enable stepless control of the airflow. The air curtain together with the intelligent FC control system allows you to easily optimize your comfort and save energy.

The recommended installation height varies depending on the relevant premises.

The control system is ordered separately.

Technical parameters

Installation		
Maximum installation height	3.5	m
Nominal data		
Color casing	Traffic white	
Color casing, RAL	RAL 9016	
Color, outlet grilles	Telegrey 2	
Color outlet grilles, NCS	S 5005-B20G	
Color outlet grilles, RAL	RAL 7046	
Enclosure class	IP20	
Ambient working temperature (dry conditions)	-20 to 30	°C
Dimensions and weights		
Length	1,057	mm
Height	302	mm
Depth	638	mm
Weight	42.4	kg
Air flow		
Air flow	1900; 1600; 1000	m³/h
Sound data		
Sound level	59; 54; 43	dB(A)
Sound power level LWA	75	dB(A)
Motor/control supply		
Control/motor supply	230	V
Phases, motor	1~	
Control/motor current, 50 Hz	2.3	A
Input power (P1), motor 50Hz	340	W
Control/motor current, 60 Hz	2.3	A
Input power (P1), motor 60Hz	340	W
Enclosure class, motor	IP20	
Insulation class	B	

Water data		
Water heating full output 40/30 °C, air +18 °C	8	kW
Pressure drop water 40/30 °C, air +18 °C	8	kPa
Water temperature	max 130	°C
Maximum working pressure	16	bar
Dimension water connections	DN20	

Parameter		
Power	25.49	kW
Air flow	1900	m³/h
Inlet air temperature	20	°C
Outlet air temperature	59	°C
Water flow	0.311	l/s
Air pressure drop	50	Pa
Inlet air humidity	70.0	% r.H
Outlet air humidity	8.0	% r.H
Water pressure drop	8.1	kPa
Inlet fluid temperature	80	°C
Outlet water temperature	60	°C
Fluid	fluidType_0	
Glycol	-	

Accessories

AR35XTT10 Air extension (19070)	DTV200S Filter pressure guard (17597)
FCBA Control for air curtain (74687)	FCDA Control for air curtain (74684)
FCPA Control for air curtain (74686)	FCSA Control for air curtain (74685)
PA34CB15 Ceiling brackets (18059)	PA34TR15 Threaded bars (18056)
PA34VD15 Vibration damper (18065)	VPFC15LF Valve system DN15LF (238293)
VPFC15NF Valve system DN15NF (238294)	VPFC20 Valve system DN20 (238295)
VPFC25 Valve system DN25 (238296)	VPFC32 Valve system DN32 (238297)

Documents

Catalogue pages Arden 3500
Manual Arden 3500
Declaration of Conformity ARFEC3500
UKCA Declaration ARFEC3500
Exploded view ARFEC35