

RDFEC15A Air curtain Ruwen

Article number: FE10193



Description

Discreet and energy-efficient air curtain for revolving doors.

Ruwen is a customized air curtain installed above your revolving door, with the exhaust duct adapted to the diameter of the door. The air curtain is equipped with energy-efficient EC motors which enable stepless control of the airflow. Together with the intelligent FC control system, the air curtain allows you to easily optimize your comfort and save energy.

The control system is ordered separately.

Technical parameters

Nominal data	
Enclosure class	IP20
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	1,560 mm
Weight	130 kg
Air flow	
Air flow	3500; 2950; 1800 m ³ /h
Sound data	
Sound level	64; 60; 47 dB(A)
Sound power level LWA	80 dB
Motor/control supply	
Control/motor supply	230 V
Control/motor current, 50 Hz	4.1 A
Input power (P1), motor 50Hz	675 W
Control/motor current, 60 Hz	4.1 A

Accessories

FCBA Control for air curtain (74687)
FCPA Control for air curtain (74686)

FCDA Control for air curtain (74684)
FCSA Control for air curtain (74685)

Documents

Catalogue pages Ruwen
Manual Ruwen
Declaration of Conformity RDFEC
UKCA Declaration RDFEC