



Description

Discreet and energy-efficient air curtain for revolving doors. Ruwen is a customized air curtain installed above your revolving door, with the exhaust duct adapted to the diameter of the door. The air curtain is equipped with energy-efficient EC motors which enable stepless control of the airflow. Together with the intelligent FC control system, the air curtain allows you to easily optimize your comfort and save energy. The control system is ordered separately.

Technical parameters

Nominal data		
Enclosure class	IP20	
Ambient working temperature (dry conditions)	-20 to 30	°C
Dimensions and weights		
Length	2,560	mm
Weight	200	kg
Air flow		
Air flow	6150; 5150; 3100	m³/h
Sound data		
Sound level	67; 62; 50	dB(A)
Sound power level LWA	83	dB(A)
Motor/control supply		
Control/motor supply	230	V
Control/motor current, 50 Hz	6.9	A
Input power (P1), motor 50Hz	1,200	W
Control/motor current, 60 Hz	6.9	A
Electric heat		
Input power, heater	29.7; 19.8; 9.9	kW
Current heating	42.9	A
Voltage heating	400	V
Phases	3~	
Temperature rise, maximum heat output, highest airflow	14	°C
Temperature rise, maximum heat output, middle airflow	17	°C
Temperature rise, maximum heat output, lowest airflow	29	°C
Parameter		
Power	29.70 kW	
Air flow	6150 m³/h	
Inlet air temperature	20 °C	
Outlet air temperature	34 °C	
Inlet air humidity	70.0 % r.H	
Outlet air humidity	30.0 % r.H	

Accessories

FCBA Control for air curtain (74687)	FCDA Control for air curtain (74684)
FCPA Control for air curtain (74686)	FCSA Control for air curtain (74685)

Documents

Catalogue pages Ruwen
Manual Ruwen
Declaration of Conformity RDFEC
UKCA Declaration RDFEC