

SIFEC15A-H Air curtain Sierra

Article number: FE10229



Description

Unique energy-efficient air curtain for exclusive establishments.

Sierra has a striking design suitable for exclusive establishments. In stainless steel with the finish or the colour of your choice, Sierra is customized to perfectly fit your entrance and make it unique. The recommended installation height is 3,5 m (varies depending on the relevant premises).

The air curtain is equipped with energy-efficient EC motors which enable stepless control of the airflow. Together with the intelligent FC control system, the air curtain allows you to easily optimize your comfort and save energy.

The control system is ordered separately.

Find more details in our online catalogue

Technical parameters

Installation		
Maximum installation height	3,500	mm
Nominal data		
Enclosure class	IP20	
Ambient working temperature (dry conditions)	-20 to 30	°C
Dimensions and weights		
Length	1,624	mm
Height	393	mm
Depth	363	mm
Weight	60	kg
Air flow		
Air flow	2750; 2250; 1400	m³/h
Sound data		
Sound level	63; 59; 48	dB(A)
Sound power level LWA	79	dB(A)
Motor/control supply		
Control/motor supply	230	V
Phases, motor	1~	
Control/motor current, 50 Hz	3.2	A
Input power (P1), motor 50Hz	510	W

Accessories

FCBA Control for air curtain (74687)
FCPA Control for air curtain (74686)
PA34CB15 Ceiling brackets (18059)
PA34VD15 Vibration damper (18065)
SIFWBB Wall bracket brushed (251886)
SIFWBP Wall bracket polished (251887)

FCDA Control for air curtain (74684)
FCSA Control for air curtain (74685)
PA34TR15 Threaded bars (18056)
PA34WS15 Wire suspension (18062)
SIFWBMP Wall bracket mirrorp (251888)

Documents

Catalogue pages Sierra
Drilling template Sierra SIFEC V 1:1
Manual Sierra
Declaration of Conformity SIFEC
UKCA Declaration SIFEC