

SIFEC25A-V Air curtain Sierra

Article number: FE10233



Description

Unique energy-efficient air curtain for exclusive establishments.

Sierra has a striking design suitable for exclusive establishments. In stainless steel with the finish or the colour of your choice, Sierra is customized to perfectly fit your entrance and make it unique. The recommended installation width is 5 m with air curtains mounted on both sides of the opening (varies depending on the relevant premises).

The air curtain is equipped with energy-efficient EC motors which enable stepless control of the airflow. Together with the intelligent FC control system, the air curtain allows you to easily optimize your comfort and save energy.

The control...

Find more details in our online catalogue

Technical parameters

Nominal data		
Enclosure class	IP20	
Ambient working temperature (dry conditions)	-20 to 30	°C
Dimensions and weights		
Length	2,608	mm
Height	393	mm
Depth	363	mm
Weight	82	kg
Air flow		
Air flow	4500; 3800; 2400	m³/h
Sound data		
Sound level	67; 63; 49	dB(A)
Sound power level LWA	83	dB(A)
Motor/control supply		
Control/motor supply	230	V
Phases, motor	1~	
Control/motor current, 50 Hz	5.1	A
Input power (P1), motor 50Hz	880	W

Accessories

AXP300 Hit protection (10028)

FCDA Control for air curtain (74684)

FCSA Control for air curtain (74685)

FCBA Control for air curtain (74687)

FCPA Control for air curtain (74686)

SIFEH Extension hood (FE10234)

Documents

Catalogue pages Sierra

Drilling template Sierra SIFEC V 1:1

Manual Sierra

Declaration of Conformity SIFEC

UKCA Declaration SIFEC