

SIFEC25WL-V Aircurtain Sierra

Article number: FE10226



Description

Unique energy-efficient air curtain for exclusive establishments.

Sierra has a striking design suitable for exclusive establishments. In stainless steel with the finish or the colour of your choice, Sierra is customized to perfectly fit your entrance and make it unique. The recommended installation width is 5 m with air curtains mounted on both sides of the opening (varies depending on the relevant premises).

The air curtain is equipped with energy-efficient EC motors which enable stepless control of the airflow. Together with the intelligent FC control system, the air curtain allows you to easily optimize your comfort and save energy.

The control...

Find more details in our online catalogue

Technical parameters

Nominal data		
Color casing	Stainless steel	
Color outlet grilles, RAL	RAL 9005	
Enclosure class	IP20	
Ambient working temperature (dry conditions)	-20 to 30	°C
Dimensions and weights		
Length	2,608	mm
Height	393	mm
Depth	363	mm
Weight	101	kg
Air flow		
Air flow	4250; 3600; 2200	m³/h
Sound data		
Sound level	67; 63; 49	dB(A)
Sound power level LWA	83	dB(A)
Motor/control supply		
Control/motor supply	230	V
Phases, motor	1~	
Control/motor current, 50 Hz	5.1	A
Input power (P1), motor 50Hz	880	W
Control/motor current, 60 Hz	5.1	A
Input power (P1), motor 60Hz	880	W
Electric heat		
Temperature rise, maximum heat output, highest airflow	17	°C
Temperature rise, maximum heat output, middle airflow	18	°C
Temperature rise, maximum heat output, lowest airflow	22	°C
Water data		
Water heating full output 60/40 °C, air +18 °C	25	kW
Water temperature	max 120	°C
Dimension water connections	DN25	

Parameter		
Power		40.46 kW
Air flow		4250 m³/h
Inlet air temperature		20 °C
Outlet air temperature		48 °C
Water flow		0.494 l/s
Air pressure drop		57 Pa
Inlet air humidity		70.0 % r.H
Outlet air humidity		14.0 % r.H
Water pressure drop		34.3 kPa
Inlet fluid temperature		80 °C
Outlet water temperature		60 °C
Fluid		fluidType_0
Glycol		-

Accessories

AXP300 Hit protection (10028)	FCBA Control for air curtain (74687)
FCDA Control for air curtain (74684)	FCPA Control for air curtain (74686)
FCSA Control for air curtain (74685)	FCWTA Water temp sensor (74702)
FH1025 Flexible hose kit DN25 (330955)	SIFEH Extension hood (FE10234)
VPFC15LF Valve system DN15LF (238293)	VPFC15NF Valve system DN15NF (238294)
VPFC20 Valve system DN20 (238295)	VPFC25 Valve system DN25 (238296)
VPFC32 Valve system DN32 (238297)	

Documents

Catalogue pages Sierra
Drilling template Sierra SIFEC V 1:1
Manual Sierra
Declaration of Conformity SIFEC
UKCA Declaration SIFEC