



TECHNICAL FOLDER

POLITEX A20

Specifications

Code	SF100R4
Name	A20
Description	SYNTHETIC FILTER MEDIA

Applications

Ventilation and industrial civil conditioning plants. Pre-filtration and separation of particulates with medium high granulometry.

Sizes

dimensions	roll 1x40	m
------------	-----------	---

Technical data

composition	polyester fiber	
regeneration	yes	
nominal thickness	6-9	mm
max. working temperature	100	°C
max. working R.H.	100	%
nominal weight	100	g/m ²
advisable cross speed	1,5	m/s
initial pressure drop	15	Pa
final pressure drop	250	Pa
average gravimetric efficiency	79,5	%
dust holding capacity	489	g/m ²
classification (EN 779:2012)	G2	
flame resistance	F1 - DIN.53438	

Rev. 01_12

GENERAL FILTER HEADQUARTER

Via Emilia, 23
31038 Paese (TV), Italia
Tel: +39 0422 4594
Fax: +39 0422 459590
www.generalfilter.com
info@generalfilter.com

GENERAL FILTER ITALIA

Via Morgagni, 40 int. 7/8
20010 Pogliano Milanese (MI), Italia
Tel: +39 02 93250640
Fax: +39 02 93255670
Italia: sales.ita@generalfilter.com
Estero: sales.int@generalfilter.com

GENERAL FILTER FRANCE

13 Avenue d'Aygu
26200 Montlimar, France
Tel: +33 987876598
Fax: +33 987876599
r.meucci@generalfilter.fr

GENERAL FILTER IBERICA

Calle Salamanca 21
28500 Arganda del Rey, Madrid,
España
Tel: +34 91 8719046
Fax: +34 91 8719054
gefisa@generalfilter.com

GENERAL FILTER HAVAK

Sanayi Sitesi P. Blok No. 10
Hosdere Mevkii
34517 Esenyurt, Istanbul, Türkiye
Tel: +90 212 623 0074
Fax: +90 212 623 0075
info@generalfilterhavak.com