

**TECHNICAL FOLDER**
**POLITEX A30**
**Specifications**

<b>Code</b>	SF250BR4
<b>Name</b>	A30
<b>Description</b>	SYNTHETIC FILTER MEDIA

**Applications**

Ventilation and industrial civil conditioning plants. Pre-filtration and separation of particulates with medium high granulometry.

**Sizes**

dimensions	roll 2x20	m
------------	-----------	---

**Technical data**

composition	polyester fiber	
regeneration	yes	
nominal thickness	15-17	mm
max. working temperature	100	°C
max. working R.H.	100	%
nominal weight	180	g/m <sup>2</sup>
advisable cross speed	1,5	m/s
initial pressure drop	35	Pa
final pressure drop	250	Pa
average gravimetric efficiency	89,8	%
dust holding capacity	473	g/m <sup>2</sup>
classification (EN 779:2012)	G3	
flame resistance	F1 - DIN.53438	

Rev. 01\_12

**GENERAL FILTER HEADQUARTER**

Via Emilia, 23  
 31038 Paese (TV), Italia  
 Tel: +39 0422 4594  
 Fax: +39 0422 459590  
 www.generalfilter.com  
 info@generalfilter.com

**GENERAL FILTER ITALIA**

Via Morgagni, 40 int. 7/8  
 20010 Pogliano Milanese (MI), Italia  
 Tel: +39 02 93250640  
 Fax: +39 02 93255670  
 Italia: sales.ita@generalfilter.com  
 Estero: sales.int@generalfilter.com

**GENERAL FILTER FRANCE**

13 Avenue d'Aygu  
 26200 Montlimar, France  
 Tel: +33 987876598  
 Fax: +33 987876599  
 r.meucci@generalfilter.fr

**GENERAL FILTER IBERICA**

Calle Salamanca 21  
 28500 Arganda del Rey, Madrid,  
 España  
 Tel: +34 91 8719046  
 Fax: +34 91 8719054  
 gefisa@generalfilter.com

**GENERAL FILTER HAVAK**

Sanayi Sitesi P. Blok No. 10  
 Hosdere Mevkii  
 34517 Esenyurt, Istanbul, Türkiye  
 Tel: +90 212 623 0074  
 Fax: +90 212 623 0075  
 info@generalfilterhavak.com